

Commercial Refrigeration Service

2501 West Behrend Drive Suite 39
Phoenix, AZ 85027-4148
(623) 869-8881 or toll free at (866) Ice Maker
FAX (623) 869-8882

Visit us on the web at WWW.IceCubes.NET

Distributors of



Commercial Ice & Beverage Systems

MGR MINI BAGGING ICE DISPENSERS



GENERAL SPECIFICATIONS

- INTERIOR: STAINLESS STEEL, TYPE 304 TANK, FULLY WELDED SEAMS.
- EXTERIOR: POLISHED STAINLESS STEEL or STUCCO ALUMINUM. GALVANIZED STEEL BACK and BOTTOM (STAINLESS STEEL OPTIONAL).
- INSULATION: 2" FOAMED IN PLACE URETHANE (NON-CFC)
- DRAIN: 1/2" MPT, BOTTOM.
- LEGS: STAINLESS STEEL PIPE LEGS WELDED INTO AN ANGLE IRON
- FRAME: ADJUSTABLE STAINLESS STEEL FEET.
- DELIVERY SYSTEM SPIRAL AUGER TYPE, STAINLESS STEEL CONSTRUCTION.
- ELECTRICAL: 115v/60hz/1ph (1) 3/4 HP GEAR MOTOR, 10.8 AMPS.
- OPTIONS: BAG BLOWER, PORTION TIMER, BAG TAPER, COIN OR TOKEN MECHANISM.

Commercial Refrigeration Service

2501 West Behrend Drive Suite 39
Phoenix, AZ 85027-4148
(623) 869-8881 or toll free at (866) Ice Maker
FAX (623) 869-8882

Visit us on the web at WWW.IceCubes.NET

Distributors of



Commercial Ice & Beverage Systems

Key Benefits

- MINI SD SERIES - GREAT FOR BEVERAGE STORES, CONVENIENCE STORES, GAS STATIONS OR ANY LOCATION WISHING TO USE OR BAG DISPENSED ICE.
- AUTOMATIC - ICE IS DISPENSED BY FOOT PEDAL CONTROL .
- DELIVERY SYSTEM - STAINLESS STEEL DELIVERY AUGER DRIVEN BY A HEAVY DUTY GEAR MOTOR THROUGH A ROLLER CHAIN DRIVE SYSTEM.
- AGITATION SYSTEM - ALL STAINLESS STEEL AGITATOR IS POWERED THE SAME GEAR MOTOR THROUGH A CONNECTING ROLLER CHAIN DRIVE SYSTEM.
- SERVICEABILITY - THE ENTIRE UNIT IS SERVICEABLE FROM THE FRONT AND REAR. ALL SHAFTS CAN BE REMOVED FROM THE FRONT. THIS ELIMINATES SIDE CLEARANCE AND MINIMIZES SPACE REQUIRED FOR REAR CLEARANCE (12").



HEAVY DUTY DELIVERY AUGER AND AGITATOR FOR TROUBLE-FREE OPERATION

Model Specifications

<u>MODEL</u> <u>NUMBER</u>	<u>APPROX</u> <u>STORAGE</u> <u>(lbs.)</u>	<u>WIDTH</u> <u>(in.)</u>	<u>DEPTH</u> <u>(in.)</u>	<u>HEIGHT</u> <u>(in.)</u>
-------------------------------	--	------------------------------	------------------------------	-------------------------------

SD-650	650	34¼	30	78
SD-900	900	48¼	30	78

Height includes 32" for stand which can be taller or shorter.

*For overall depth, add 16" for front nozzle and rear cover.

Allow 12" behind unit for servicing.